



SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name:

| Sakrete Portland Cement |
|-------------------------------|
| Sakrete Type N Masonry Cement |
| Sakrete Type S Masonry Cement |

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

| 11 | c | Δ | ٠ | |
|----|---|---|---|--|
| U | Э | c | | |

Various.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

| Name/Address: | Sakrete of North America 8201 Arrowridge Blvd. Charlotte, NC 28273 | |
|------------------------|---|--|
| Telephone Number: | 866-725-7383 | |
| 1.4 EMERGENCY TELEPHON | IE NUMBER | |
| Emergency Telephone | CHEMTREC 800-424-9300 | |

Emergency Telephone
Number:CHEMTREC 800-424-9300
INTERNATIONAL + 01-703-527-3887Date of Preparation:February 1, 2013Version #: 1.0


Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class

Acute toxicity 4 (Oral) Skin irritation 2 Serious eye damage 1 Skin sensitization 1 Carcinogenicity 1A Specific target organ toxicity - Single exposure 3 Specific target organ toxicity - Repeated exposure 1

2.2 LABEL ELEMENTS





AKRETE

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

SAFETY DATA SHEET

use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust.

Response: If swallowed: Immediately call a poison center/doctor. Rinse mouth. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed. **Disposal:** Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

| Hazards not otherwise | |
|-----------------------|-----------------|
| classified: | Not applicable. |

60.0 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

| Ingredient | UN # | H / F/ R / * | CAS No | Wt. % |
|-----------------------------|----------------|----------------|------------|----------|
| Portland cement | Not available. | 1/0/0 | 65997-15-1 | 60 - 100 |
| Ferric oxide | UN1376 | 1/0/0 | 1309-37-1 | 10 - 30 |
| Silica, crystalline, quartz | Not available. | Not available. | 14808-60-7 | 3 - 7 |
| Calcium oxide | UN1910 | 3/0/1 | 1305-78-8 | 3 - 7 |
| Gypsum | UN3077 | Not available. | 13397-24-5 | 3 - 7 |
| Calcium carbonate | Not available. | 1/0/0 | 1317-65-3 | 3 - 7 |
| Magnesium oxide | UN1418 | 2/0/0 | 1309-48-4 | 3 - 7 |

The exact percentage (concentration) of chemicals has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

* Per NOM-018-STPS-2000

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.





SAFETY DATA SHEET

| Skin: | In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists. |
|----------------------------|--|
| Inhalation: | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| Ingestion: | If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention. |
| 4.2 MOST IMPORTANT SYMPT | OMS AND EFFECTS, BOTH ACUTE AND DELAYED |
| Eye: | Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. |
| Skin: | Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact. |
| Inhalation: | May cause respiratory tract irritation. |
| Ingestion: | Harmful if swallowed. May cause stomach distress, nausea or vomiting. |
| 4.3 INDICATION OF ANY IMME | DIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED |
| Note to Physicians: | Symptoms may not appear immediately. |
| Specific Treatments: | In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible). |
| | Section 5: FIRE-FIGHTING MEASURES |
| | |

5.1 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Treat for surrounding material.

Unsuitable Extinguishing Media: Not available.

5.2 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

5.3 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.





CUSTOMER SERVICE (734) 782-2073

Conforms to OSHA HazCom 2012, CPR & NOM-018-STPS-2000 Standards

SAFETY DATA SHEET

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

| | Section 7: HANDLING AND STORAGE |
|--------------------------|--|
| Methods for Cleaning-Up: | Vacuum or sweep material and place in a disposal container. |
| Methods for Containment: | Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). |

7.1 PRECAUTIONS FOR SAFE HANDLING

| Handling: | Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking. (See section 8) |
|----------------------------|---|
| General Hygiene Advice: | Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. |
| 7.2 CONDITIONS FOR SAFE ST | FORAGE, INCLUDING ANY INCOMPATIBILITIES |
| Storage: | Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. (See section 10) |

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

| Occupational Exposure Limits | | |
|------------------------------|---|---|
| Ingredient | OSHA-PEL | ACGIH-TLV |
| | | 1 mg/m³ (no asbestos and <1% |
| Portland cement | 15 mg/m³ (total); 5 mg/m³ (resp) | crystalline silica, respirable fraction) |
| Ferric oxide | 10 mg/m ³ | 5 mg/m ³ (iron oxide fume; dust as Fe) |
| | ((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) | |
| Silica, crystalline, | ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) | |
| quartz | ((250)/(%SiO ₂ +5) mppcf TWA (resp)) | 0.025 mg/m ³ |
| Calcium oxide | 5 mg/m³ | 2 mg/m ³ |
| | 15 mg/m ³ TWA (poussière totale) | |
| Gypsum | $5 \text{ mg/m}^3 \text{ TWA}$ (fraction respirable) | 10 mg/m ³ |
| Calcium carbonate | 15 mg/m ³ (total); 5 mg/m ³ (resp) | 10 mg/m ³ |
| Magnesium oxide | 15 mg/m ³ | 10 mg/m ³ |

8.2 EXPOSURE CONTROLS

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.







SAFETY DATA SHEET

8.3 INDIVIDUAL PROTECTIVE MEASSURES

Personal Protective Equipment:

| Eye/Face Protection: | Wear approved eye (properly fitted dust- or splash-proof chemical safety |
|----------------------|--|
| | goggles) / face (face shield) protection. |

Skin Protection:

Hand Protection: Wear suitable waterproof gloves.

Body Protection: Wear suitable waterproof protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Health and Safety Measures:

Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

| Appearance: | Powder. |
|--|----------------|
| Color: | Not available. |
| Odor: | Not available. |
| Odor Threshold: | Not available. |
| Physical State: | Powder. |
| pH: | 12 - 13 |
| Melting Point/Freezing Point: | Not available. |
| Initial Boiling Point and Boiling Range: | Not available. |
| Flash Point: | Not available. |
| Evaporation Rate: | Not available. |
| Flammability: | Not Flammable. |
| Lower Flammability/Explosive Limit: | Not available. |
| Upper Flammability/Explosive Limit: | Not available. |
| Vapor Pressure: | Not available. |
| Vapor Density: | Not available. |
| Relative Density/Specific Gravity: | Not available. |
| Solubility: | Not available. |
| Partition coefficient: n-octanol/water: | Not available. |
| Auto-ignition Temperature: | Not available. |
| Decomposition Temperature: | Not available. |







SAFETY DATA SHEET

| Viscosity: |
|--------------------------|
| Percent Volatile, wt. %: |
| VOC content wit % |

Not available.

Not available.

VOC content. wt. %:

0%, Not applicable; 0 wt, Not applicable.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Incompatible materials. Moisture.

10.5 INCOMPATIBLE MATERIALS

None known.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

- Causes serious eye damage. May cause burns in the presence of Eve: moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Skin: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Acute Toxicity:

| Ingredient | IDLH | LC50 | LD50 |
|--------------------------------|---|----------------|------------------------|
| Portland cement | 5000 mg/m ³ | Not available. | Not available. |
| Ferric oxide | 2500 mg Fe/m ³ | Not available. | Oral >10000 mg/kg, rat |
| Silica, crystalline, quartz | Ca [25 mg/m ³ (cristobalite, tridymite) 50 mg/m ³ (quartz, tripoli)] | Not available. | Oral 500 mg/kg, rat |
| Calcium oxide | 25 mg/m ³ | Not available. | Oral 500 mg/kg, rat |
| Gypsum | Not available. | Not available. | Not available. |





SAFETY DATA SHEET

| Coloium | | | | | |
|---|----------------|--|----------------------------------|----------------|--------------------------|
| Calcium carbonate | Natavailable | | Notov | oiloblo | Not available. |
| | Not available. | | Not available. | | |
| Magnesium oxide | | 750 mg/m ³ | Not available. | | Oral >5000 mg/kg, rat |
| Calculated overall Chemical Acute Te | | | | ity Values | 6 |
| LC50 (inhalation) | | LD50 (oral) | l) LD50 (dermal) | | LD50 (dermal) |
| Not available. | | 1603.8 mg/kg, rat | | Not available. | |
| | | | Chemical Listed as Carcinogen or | | |
| | | | | Potenti | al Carcinogen |
| Ingredient | | (NTP, IARC, OSHA, ACGIH, CP65)* | | | |
| Portland cement | | | G-A4 | | |
| Ferric oxide | | | G-A4, I-3 | | |
| Silica, crystalline, quartz | | G-A2, I-1, N-1, CP65 | | | |
| Calcium oxide | | Not listed. | | | |
| Gypsum | | Not listed. | | | |
| Calcium carbonate | | | Not listed. | | |
| Magnesium oxide | | | G-A4 | | |
| 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE | | | | | |
| Skin Corrosion/Irrit | ation: | Causes skin irritation. May cause burns in the presence of moisture. | | | |
| Serious Eye Damage/Irritation: Causes serious eye | | Causes serious eye da | amage. Ma | ay cause | burns in the presence of |

moisture.

- **Respiratory Sensitization:** Based on available data, the classification criteria are not met.
- Skin Sensitization: May cause an allergic skin reaction.
- **STOT-Single Exposure:** May cause respiratory irritation.
- Chronic Health Effects: Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
 - Carcinogenicity: May cause cancer.
 - Germ Cell Mutagenicity: This product is not classified as a mutagen.

Reproductive Toxicity:

| Developmental: | Based on available data, the classification criteria are not met. |
|---|---|
| Fertility: | Based on available data, the classification criteria are not met. |
| STOT-Repeated Exposure: | Causes damage to organs through prolonged or repeated exposure. |
| Aspiration Hazard: | Based on available data, the classification criteria are not met. |
| Toxicologically Synergistic Materials: | Not available. |







SAFETY DATA SHEET

| 50 | ction 12: ECOLOGICAL INFORMA | TION |
|---------------------------------------|---------------------------------|---|
| | CION 12. ECOLOGICAL INFORMA | |
| 12.1 ECOTOXICITY | | |
| Acute/Chronic Toxicity: | Normal dilution of this product | nen used according to directions. to drains, sewers, septic systems nsidered environmentally harmful. |
| 12.2 PERSISTENCE AND DEGRA | · | , |
| Not available. | | |
| 12.3 BIOACCUMULATIVE POTEN | NTIAL | |
| Bioaccumulation: | Not available. | |
| 12.4 MOBILITY IN SOIL | | |
| Not available. | | |
| 12.5 OTHER ADVERSE EFFECTS | 3 | |
| Not available. | | |
| Sec | ction 13: DISPOSAL CONSIDERA | ΓIONS |
| 13.1 WASTE TREATMENT METH | | |
| Disposal Method: | | disposed of in accordance with al |
| Disposal metriod. | | and federal regulations. |
| Other disposal recommendatio | ns: Not available. | |
| Se | ection 14: TRANSPORT INFORMA | TION |
| 14.1 UN NUMBER | | |
| DOT | TDG | NOM-004-SCT2-1994 |
| Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN PROPER SHIPPING NAM | 5 | i tot rogalatou. |
| DOT | TDG | NOM-004-SCT2-1994 |
| Not applicable. | Not applicable. | Not applicable. |
| 14.3 TRANSPORT HAZARD CLA | | |
| DOT | TDG | NOM-004-SCT2-1994 |
| | Not applicable. | Not applicable. |
| Not applicable. | | |
| Not applicable. 14.4 PACKING GROUP | | |
| | TDG | NOM-004-SCT2-1994 |
| 14.4 PACKING GROUP | TDG Not applicable. | NOM-004-SCT2-1994 Not applicable. |
| 14.4 PACKING GROUP DOT | Not applicable. | |







SAFETY DATA SHEET

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

| SARA Title III | | | | |
|-----------------------------|---------------------------------|------------------------------|---------------------|-------------|
| Ingredient | Section 302 (EHS) TPQ (lbs.) | Section 304 EHS RQ (lbs.) | CERCLA RQ (lbs.) | Section 313 |
| Portland cement | Not listed. | Not listed. | Not listed. | Not listed. |
| Ferric oxide | Not listed. | Not listed. | Not listed. | Not listed. |
| Silica, crystalline, quartz | Not listed. | Not listed. | Not listed. | Not listed. |
| Calcium oxide | Not listed. | Not listed. | Not listed. | Not listed. |
| Gypsum | Not listed. | Not listed. | Not listed. | Not listed. |
| Calcium carbonate | Not listed. | Not listed. | Not listed. | Not listed. |
| Magnesium oxide | Not listed. | Not listed. | Not listed. | Not listed. |

State Regulations

California Proposition 65:

This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

| Ingredient | USA |
|-----------------------------|-----------------------------------|
| • | TSCA |
| Portland cement | Yes. |
| Ferric oxide | Yes. |
| Silica, crystalline, quartz | Yes. |
| Calcium oxide | Yes. |
| Gypsum | No. |
| Calcium carbonate | Yes. |
| Magnesium oxide | Yes. |
| NFPA - Nation | al Fire Protection Association: |
| Health: | 3 |
| Fire: | 1 |
| Reactivity: | 0 |
| HMIS - Hazardou | s Materials Identification System |
| Health: | 3* |
| Fire: | 1 |
| Reactivity: | 0 |

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme





SAFETY DATA SHEET

Mexico Classification:

SAKRETE



| \sim | | | | |
|---------------|---|--|--|--|
| Blue = Health | Red = Flammability Yellow = Reactivity White = Special | | | |
| Hazard Rating | : 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme | | | |
| SOURCE AGE | NCY CARCINOGEN CLASSIFICATIONS: | | | |
| CP65 | California Proposition 65 | | | |
| OSHA (O) | Occupational Safety and Health Administration. | | | |
| ACGIH (G) | American Conference of Governmental Industrial Hygienists. A1 - Confirmed human carcinogen. A2 - Suspected human carcinogen. A3 - Animal carcinogen. A4 - Not classifiable as a human carcinogen. A5 - Not suspected as a human carcinogen. | | | |
| IARC (I) | International Agency for Research on Cancer. 1 - The agent (mixture) is carcinogenic to humans. 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals. 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans. | | | |
| NTP (N) | National Toxicology Program. 1 - Known to be carcinogens. 2 - Reasonably anticipated to be carcinogens. | | | |
| | Section 16: OTHER INFORMATION | | | |
| | | | | |

| Date of Preparation: | February 1, 2013 | | |
|----------------------|------------------|--|--|
| Version: | 1.0 | | |
| Revision Date: | Julv 17. 2014 | | |

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

| Prepared by: | Nexreg Compliance Inc. Phone: (519) 488-5126 <u>www.nexreg.com</u> |
|---------------|--|
| Prepared for: | Sakrete of North America |

End of Safety Data Sheet